

Electric Mini-Tank Point-of-Use Water HeatersGL2.5Ti • GL4Ti • GL8Ti





Mini-Tank Water Heaters for the Professional

GL2.5Ti/GL4Ti/GL8Ti

Energy-efficient electric mini-tank heaters for point-of-use or performance enhancement.

ARISTON



Easy installation and energy efficiency

The Ariston point-of-use electric mini-tank is available in three sizes. The units can be wall-hung (bracket included) or floor-mounted and come with a temperature/pressure relief valve. They have an 8-year warranty.

Simply tap into the cold water line and install the water heater directly at the sink to provide a small volume of water. They may also be installed in-line with a larger hot water source to eliminate the wait for hot water. The two smaller units have a simple 120V AC plug-in connection.

- Saves space
- Provides hot water instantly at the point-of-use
- Stand-alone or in-line application
- Temperature/pressure relief valve included
- 8-year warranty







	GL2.5Ti	GL4Ti	GL8Ti
Tank Volume	2.75 gallons	3.85 gallons	7 gallons
Dimensions	14"×14"×101/4"	14"×14"×12¼"	17½"x17½"x14½"
Voltage	120V AC	120V AC	120V AC
Amperage	12.5 amps	12.5 amps	12.5 amps
Wire Size	Plug-in	Plug-in	Hard-wired
Heating Capacity	1500 watts	1500 watts	1500 watts
Recovery at 90°F Rise	6.8 gph	6.8 gph	6.8 gph
Temperature Range	65°-145°F	65°-145°F	65°-145°F
Water Connections	½" NPT	½" NPT	3/4" NPT
Operating Pressure	150 psi	150 psi	150 psi
Relief Valve	Installed	Installed	Included
Part #	GL2.5Ti	GL4Ti	GL8Ti

gph = gallons per hour






Stand-alone


Installation

No waiting for hot water

Every year billions of gallons of water are wasted turning on the faucet and waiting for hot water to arrive. Save water by installing an Ariston ProTI under the sink and eliminate the wait for hot water to reach the tap without the need to install costly recirculating lines and pumps.







50 Wentworth Avenue Londonderry, NH 03053

Tel: 1-866-642-3198 Fax: 1-603-584-1681 www.boschpro.com



